

UNITED STATES PATENT APPLICATION

OF

MOO-JONG LIM

AND

HYUNG-KI HONG

FOR

**METHOD OF COLOR IMAGE DISPLAY FOR
A FIELD SEQUENTIAL LIQUID CRYSTAL DISPLAY DEVICE**

**LONG ALDRIDGE & NORMAN LLP
701 PENNSYLVANIA AVENUE, N.W.
SUITE 600, SIXTH FLOOR
WASHINGTON, D.C. 20004
(202) 624-1200**

0998631 11001
106011 1198660

5 Field of the Invention

Discussion of the Related Art

[0004] Generally, a liquid crystal display (LCD) device includes an upper substrate, a lower substrate, and a liquid crystal layer interposed between the upper and lower substrates. The upper and lower substrates respectively have electrodes opposing to each other. When an electric field is applied between the electrodes of the upper

substrate and the electrodes of the lower substrate, molecules of the liquid crystal are aligned according to the electric field. By controlling the electric field, the liquid crystal display device provides varying transmittance of the light of incident to the display images.

5 [0005] Currently, an active-matrix liquid crystal display (AM LCD) device is the most popular because of its high resolution and superiority in displaying moving images. A typical active-matrix liquid crystal display has a plurality of switching elements and pixel electrodes, which are arranged in an array matrix on the lower substrate.

10 Therefore, the lower substrate of the active-matrix liquid crystal display is alternatively referred to as an array substrate.

[0006] The structure of a conventional active-matrix liquid crystal display will be described hereinafter with reference to FIG. 1, which illustrates a cross-section of a pixel region. The active-matrix liquid crystal display 10 consists of a liquid crystal panel 15 and back light 50. The liquid crystal panel 15 includes a color filter substrate (an upper substrate) 20 and an array substrate (a lower substrate) 40 which face each other across a liquid crystal layer 30. A color filter layer 22, which includes a black matrix 22b for excluding a leakage of light and sub-color-filters 22a, consisting of red (R), green (G), and blue (B), is formed on the color filter substrate 20. A common electrode 24 is formed on the color filter layer 22 as one of electrodes for applying a voltage to the liquid crystal layer 30. A thin film transistor, for functioning as a switching element, and a pixel region are formed on the array substrate 40 facing the color filter substrate 20. A pixel electrode 42, electrically connected to the thin film

transistor and functioning as another electrode in applying a voltage to the liquid crystal layer 30, is formed on the array substrate 40. The back light 50 is disposed under the array substrate 40 to irradiate light to the liquid crystal panel 15. This liquid crystal display device uses optical anisotropy and polarization properties of liquid crystal molecules for displaying a desired image. That is, applying a voltage to the liquid crystal molecules having a thin and long structure and a pretilt angle changes an alignment direction of the liquid crystal molecules. Thereafter, incident light from the back light is polarized due to the optical anisotropy of the liquid crystal molecules. And lastly, the polarized light is modulated by passing through the color filter layer and thus color images are displayed. The thin film transistor includes a gate electrode and a source and a drain electrodes (not shown).

[0007] But the conventional active-matrix liquid crystal display device has some problems. First, the material used for the color filter is expensive and the methods for manufacturing the color filter require more material to be consumed in the manufacturing process, resulting in an increase in the manufacturing cost. Second, the maximum value of a transmissivity of a material used for the color filter is 33%, so that a brighter back light needs to be used in order to display a color image effectively, which results in the increase of the power consumption. Last, when the color filter is thick, properties of color are fine, but the transmissivity is decreased. On the other hand, when the color filter is thin the transmissivity can be raised but, the color properties will become poor. Therefore, a manufacturing process having great

precision is required for the color filter, which results in a decrease in production yield and an increase in the rate of inferior goods.

[0008] Many studies and experiments have been conducted recently, and a field sequential liquid crystal display device, able to display a full color without the color filter, is suggested as an alternative. The field sequential liquid crystal display devices display a color image by turning on light sources Red, Green and Blue sequentially during a frame, whereas the conventional active-matrix liquid crystal display devices display the color image by a white light source of the back light that is constantly turned on. The field sequential liquid crystal display device has not been popular until recently because of poor response time. However, development of new liquid crystal modes such as Ferroelectric Liquid Crystal (FLC), Optical Compensated Birefringent (OCB) and Twisted Nematic (TN) having a high response time of the liquid crystal can result in more wide spread use of the field sequential liquid crystal. In addition, the Optical Compensated Birefringent (OCB) mode is generally used for the field sequential liquid crystal display device. Both surfaces of an upper and a lower substrates are rubbed in a same direction and thereafter a voltage is applied to form a band-structure of the liquid crystal in OCB mode. Because the movement of liquid crystal molecules becomes faster when the voltage is applied to the liquid crystal, the response time of the liquid crystal becomes fast-within about 5m/sec. Accordingly, the liquid crystal cell of the OCB mode is suitable for the field sequential liquid crystal display device because of its high response time leaving no residual image on a screen.

[0009] FIG. 2 is a cross-sectional view illustrating the schematic cross section of the conventional field sequential liquid crystal display device. The conventional field sequential liquid crystal display device 60 includes an upper substrate 64 (referred to as a color filter substrate), a lower substrate 66 (referred to as an array substrate), a liquid crystal layer 70 interposed the upper and lower substrates and a back light 72 consisting of three light sources Red, Green and Blue to irradiate light to the liquid crystal panel 62. A black matrix 61 is formed between the common electrode 65 and a transparent substrate 1 of the upper substrate 64 in order to intercept light in a region other than a region of the common electrode ^{e 65} 67. A thin film transistor functioning as a switching element and electrically connected to the pixel electrode is formed on the lower substrate 66. The thin film transistor consists of a gate electrode and a source electrode and a drain electrode (not shown). The major difference of the field sequential liquid crystal display device 60 with the previous conventional liquid crystal display is that the field sequential liquid crystal display device does not need the color filters and has the back light having three light sources selectively turned on and off. The light sources Red, Green and Blue are driven respectively by an inverter (not shown) and each of light sources Red, Green and Blue is turned on and off one hundred and eighty times per second, and thus a color image is displayed using a residual image effect of eyes caused by the mixture of three colors, red, green and blue. Even though the light source is turned on and off one hundred and eighty time per second, to the naked eye the light source appears to be kept on. For example, if the light source Red is turned on and then the light source Blue is turned on, a mixed color violet is seen owing to the

residual image effect. Whereas a total luminance of the conventional active-matrix liquid crystal display device is low owing to the low transmissivity of the color filter, the field sequential liquid crystal display device overcomes this problem because it does not have a color filter. In addition, the field sequential liquid crystal display device is suitable for a large scale liquid crystal display device because it can display a full-color using three color light sources, whereby it can display an image of high luminance and high resolution. Even though the conventional active-matrix liquid crystal display device is inferior to CRT (Cathode Ray Tube) in terms of price or clearness, the field sequential liquid crystal display device can settle these problems.

[0010] FIG. 3A is a cross-sectional view illustrating a wave guide type back light of the field sequential liquid crystal display device; FIG. 3B is a cross-sectional view illustrating a directly underlaid type back light of the field sequential liquid crystal display device. The wave guide type back light has light sources Red, Green and Blue disposed in a row at one edge or both edges of the liquid crystal panel 62 and diffuses light using a light guide panel and reflector. The wave guide type back light 74 may use a Cold Cathode Fluorescent Lamp (CCFL) as a light source and is suitable for notebook computers or the like because of its low weight and power consumption. The directly underlaid type back light 76 has light sources Red, Green and Blue 75 disposed in a repeated sequence of Red, Green and Blue under a scattering film 77 and irradiates light directly to the whole surface of the liquid crystal panel 62. The directly underlaid type back light is usually used for the image display device where the luminance is

important and has a high power consumption because of its relatively big thickness and high ratio of diffusion.

09985534 " 410901

[0011] FIG. 4A is a plane view showing a part of an array substrate. A plurality of horizontal gate bus lines 78 and vertical data bus lines 80 crossing gate bus lines are formed on the array substrate, and a thin film transistor is formed at every intersection of gate bus lines and data bus lines. A pixel electrode 79 electrically connected to the thin film transistor is formed on the array substrate. The conventional field sequential liquid crystal display device is driven by applying an image signal data to the data line 80 and scanning an electric pulse to the gate line 78. A line sequential driving method is used for the field sequential liquid crystal display device in order to improve a quality of an image, where a gate scan input driver applies a gate pulse voltage to one of gate lines at a time and applies the gate pulse voltage sequentially to the next gate line. One frame is completed when the gate pulse voltage is applied to all gate lines. That is, if the gate pulse voltage is applied to nth gate line 78, all of thin film transistors connected to the nth gate line 78 are turned on, and the image signal of the data line 80 is accumulated in liquid cells and in storage capacitors through the thin film transistor that have been turned on. Accordingly, liquid crystal molecules are realigned according to the image signal data accumulated in the liquid crystal cell and an image signal voltage, and then a desired image is displayed after the light from the back light passes through the liquid crystal cell.

[0012] FIG. 4B is a time chart showing a driving method of the conventional field sequential liquid crystal display device. The driving sequence of the conventional field

sequential liquid crystal display device is as follows. After all thin film transistors for one of the light sources are turned on sequentially, the liquid crystal molecules become aligned according to the applied voltage, and then the next one of light sources is turned on. And the same process is repeated for other remaining light sources. Each of light sources Red, Green and Blue is driven one time respectively for a frame. The driving process of each of the light sources must be completed respectively within one period of sub-frame, i.e. $1/4f$. Taking one of light sources for example, a period of a sub-frame consists of a scanning time, a response time of the liquid crystal and a flashing time of the back light, and this relation can numerically be expressed as follow:

$$1/4f = t_{TFT} + t_{LC} + t_{BL}$$

where f is a frame frequency, t_{TFT} (92) is a scanning time for all thin film transistors of sub-frame, t_{LC} (94) is a response time of the assigned liquid crystal and t_{BL} (96) is a flash time of the back light. If the frame frequency t_{TFT} (92) is increased, whereas the flash time t_{BL} (96) is kept constant, the response time t_{LC} (94) decreases because the time period of one sub-frame is fixed. If the response time t_{LC} (94) is decreased, and thus an actual response time of the liquid crystal becomes longer than the assigned response time of the liquid crystal, the back light is driven before the proper alignment of the liquid crystal occur, causing screen color to not be uniform.

[0013] FIG. 5 is a schematic diagram illustrating a sequence of color image display for one frame in the conventional field sequential liquid crystal display device. The one frame period of the field sequential liquid crystal display device is $1/60$ second, and the sub-frame period for each of the light sources Red, Green and Blue is one-third of the

one frame period, i.e., 1/180 second (5.5msec). The actual lighting time of each of light sources Red, Green and Blue for a sub-frame becomes shorter than 1/180 second because color interference may happen when light sources Red, Green and Blue are driven as on-state continuously. As shown in the figure, a sequence for color image display for the field sequential liquid crystal display device is as follow. One frame "F" is divided into three sub-frames S1, S2 and S3 for each of the light sources Red, Green and Blue, and each of the light sources is sequentially turned on and off in order to display a color image by irradiating light to the liquid crystal panel (62).

[0014] FIG. 6 is a schematic diagram illustrating a sequence of color image display for one frame in the conventional field sequential digital light processing (DLP) device used for a projector, for example. The field sequential digital light processing device uses four light sources Red, Green, Blue and White. Because the field sequential digital light processing device irradiates light using a principle of reflection of mirror, it has a high efficiency of use of light and can display an image of higher luminance than a transmissive type of liquid crystal display device irradiating light from behind the liquid crystal panel. Because every control is accomplished digitally, and the device has a single plate structure, it is suitable for minimization of products. The field sequential digital light processing device controls a refraction ratio using an non-light emitting element instead of the liquid crystal. As shown in the figure, one frame "F" is divided into four sub-frames Sa, Sb, Sc and Sd for each of light sources Red, Green, Blue and White. Each of light sources is sequentially turned on and off in order to display a color image by irradiating light to the digital light processing panel (82). One

5

[0015] Accordingly, the present invention is directed to a field sequential liquid crystal display device and a method of color image display for a field sequential liquid crystal display device that substantially obviates one or more of problems due to limitations and disadvantages of the related art.

10

15

20

[0019] To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described, a field sequential liquid crystal display device comprises a liquid crystal panel having an upper substrate, a lower substrate and a liquid crystal layer disposed therebetween, a back light disposed under the liquid crystal panel and irradiating a light to the liquid crystal panel and having 3 different light sources Red, Green and Blue sequentially driven; and an image signal processor controlling a lighting speed of each of light sources Red, Green and Blue. The liquid crystal mode is Optically Compensated Birefringence (OCB) mode. Each of light sources Red, Green and Blue of the back light is disposed at a down edge of the liquid crystal panel or at directly under of liquid crystal panel in a repeated sequence of Red, Green and Blue. The back light further includes a fourth light source and a color of the fourth light source is within a color range from Green to Blue.

[0020] In another aspect, a method of color image display for a field sequential liquid crystal display device including an image signal processor, comprises steps of dividing a frame into four sub-frames having a period of one-fourth of one frame period, driving each of light sources Red, Green and Blue sequentially at a first, a second and a third sub-frame, and driving a light source combination with three or fewer colors of Red, Green and Blue at a fourth sub-frame. The possible combination turned on at the fourth sub-frame is one of combinations consisting of all off, R, G, B, G+B, R+B, R+G, and all on. A one frame period is 1/60 second and a lighting time of the light source at each sub-frame is shorter than 1/240 second.

[0021] In another aspect, a method of color image display for a field sequential liquid crystal display device including an image signal processor, comprises steps of dividing a frame into four sub-frames having a period of one-fourth of one frame period, driving each of light sources Red, Green and Blue sequentially at a first, a second and a third sub-frame, driving a light source combination with three or fewer colors of Red, Green and Blue at a fourth sub-frame, classifying each component R, G and B of a color image input signal using a gray level having 256 levels, deciding a maximum luminance value of the field sequential liquid crystal display device using the gray level, obtaining an average luminance value of each of component R, G and B from the image input signal, turning on one of light sources Red, Green and Blue having a larger average luminance value than the maximum luminance value at the fourth sub-frame, and converting the input luminance value of component R, G and B and an input luminance value of the fourth sub-frame using the image signal processor. The possible combination turned on at the fourth sub-frame is one of combinations consisting of all off, R, G, B, G+B, R+B, R+G, and all on. The light source which is to be turned on at the fourth sub-frame is decided on the basis of a maximum luminance value of R, G and B. The one frame period is 1/60 second and a lighting time of the light source at each sub-frame is shorter than 1/240 second.

[0022] In another aspect, a method of color image display for a field sequential liquid crystal display device including an image signal processor, comprises steps of dividing a liquid crystal panel into n number of driving areas, turning on each of light sources

Red, Green and Blue sequentially for every divided driving area, and having a time interval between driving sections of a previous light source and a next light source.

The time interval is formed from a second divided driving area. If an Optically Compensated Birefringence (OCB) mode is selected for a liquid crystal, the time interval may be 0.5msec ~ 1msec. The number n for divided driving area is dependent on a degree of a resolution of a liquid crystal display device and response time of the liquid crystal. Lighting time of a back light is also dependent on the degree of resolution of the liquid crystal display device and response time of the liquid crystal.

[0023] It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

[0024] The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention. In the drawings:

[0025] FIG. 1 is a cross-sectional view showing a cross section of a pixel of a conventional liquid crystal display device;

[0026] FIG. 2 is a cross-sectional view showing a cross section of a pixel of a conventional field sequential liquid crystal display device;

20 [0036] FIG. 10 is a plan view showing divided driving areas of the field sequential liquid crystal display device according to the present invention;

[0037] FIG. 11 is a schematic diagram illustrating a driving method for divided driving areas for the field sequential liquid crystal display device according to the present invention;

[0038] FIG. 12 is a schematic diagram showing color coordinates of a color gamut of the field sequential liquid crystal display device according to the present invention;

[0039] FIGs. 13A and 13B are schematic diagram illustrating a projector system, for example, among field sequential liquid crystal display devices according to the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0040] Reference will now be made in detail to the preferred embodiment of the present invention, which is illustrated in the accompanying drawings.

[0041] FIG. 7 is a schematic diagram illustrating a field sequential liquid crystal display device according to the present invention. The field sequential liquid crystal display device according to the present invention includes a liquid crystal panel 100 having an upper substrate and a lower substrate and liquid crystal layer disposed therebetween, a back light 110 having three light sources Red, Green and Blue and irradiating light to the liquid crystal panel 100, and an image signal processor 120 controlling a lighting ^{Speed} spec of light sources Red, Green and Blue of the back light 110.

The liquid crystal panel 100 and the back light 110 have a same structure as that of the conventional field sequential liquid crystal display device described before with respect to FIG. 2. One of Ferroelectric Liquid Crystal (FLC) mode, Optically Compensated

0998631.10001

5/17/04
HT

Birefringent (OCB) mode and Twisted Nematic (TN) mode, for example, having a high response time is used for a liquid crystal mode. In addition, a non-light emitting element, instead of the liquid crystal, may be used in Digital Light Processing (DLP) devices as described with respect to FIG. 6.

5 [0042] A method and an algorithm for controlling the lighting speed of the back light 110 using the image signal processor will be described hereinafter with reference to FIGs. 8 and 9. FIG. 8 is a schematic diagram illustrating a sequence of color image display for one frame in the field sequential liquid crystal display device according to the present invention. When image signals having information on the respective
10 components R, G and B are inputted into the field sequential liquid crystal display device, the image signal processor converts the lighting speeds of light sources Red, Green and Blue of the back light for every frame. As shown in the figure, one frame "F" is divided into four sub-frames having a period of one-fourth of one frame period. Each of light sources Red, Green and Blue 110a, 110b and 110c is turned on
15 sequentially at the first, the second and the third sub-frame "SF1", "SF2" and "SF3" and a combination of light sources of three or fewer colors of R, G and B is turned on at the fourth sub-frame in order to display a color image. The light source turned on at the fourth sub-frame is defined as a light source "X" 110d in the figure.

[0043] In detail, when a luminance of the component R is read high from the image
20 signal, the luminance of the component R may be increased by turning on the light source Red at the fourth sub-frame "SF4". If one color of Cyan, Magenta and Yellow, which are complementary colors of R, G and B, is particularly stressed among the

image signal, the luminance of the stressed color may be increased by turning on two light sources among light sources Red, Green and Blue at the fourth sub-frame "SF4". In addition, the maximum luminance of a white color may be increased by turning on all light sources Red, Green and Blue at the same time at the fourth sub-frame.

5 Accordingly, because the luminance of the stressed color may be increased and diverse colors may be displayed using the fourth sub-frame according to the present invention, the present invention can provide a liquid crystal display device having high qualities of image and can be used for devices requiring high quality images, for example, TV.

[0044] FIG. 9 is a flow chart illustrating a method for color image display for the field sequential liquid crystal display device according to the present invention, and more particularly, a method for deciding a light source which is to be turned on at the fourth sub-frame. The luminance of each component R, G and B in color image signal is expressed with a gray level having 256 levels. When the luminance of each component R, G and B has a value of gray level 127, it is set as a maximum luminance. As shown in the figure, when the image signal for a full screen is inputted, an average luminance value R_a , G_a and B_a of each of components R, G and B is calculated in ST1(step 1). Each of average luminance values R_a , G_a and B_a will be selected when it is bigger than the gray level 128. The light source which is to be turned on at the fourth sub-frame is decided in ST2 (step 2). The possible combination turned on at the fourth sub-frame is one of combinations consisting of all off, R, G, B, G+B, R+B, R+G, and all on. Input values for each sub-frame are converted in ST3 (step 3) by the image signal processor. That is, when the average luminance value R_a , G_a and B_a is bigger than the gray level

128, the light source corresponding to the component having a larger average
luminance will be turned on at the fourth sub-frame. If all of the average luminance
values R_a , G_a and B_a have values lower than the gray level 128, all light sources Red,
Green and Blue are turned off at the fourth sub-frame. In addition, if only the average
5 luminance value R_a has a value larger than the gray level 128, the image signal
expressed as $(R, G, B) = (200, 100, 100)$ may be converted to $(R, G, B, X) =$
 $(72, 100, 100, 128)$, where "X" is the light source which is to be turned on at the fourth
sub-frame. Because only the light source Red is to be turned on at the fourth sub-frame
in this example, the gray level of the component R becomes $72 + 128 = 200$. This can
10 be applied to light sources Green and Blue in same way when average luminance value
 G_a or B_a is larger than the gray level 128. If all average luminance values R_a , G_a and
 B_a are bigger than the gray level 128 ($2R_a, 2G_a, 2B_a > 255$), the image signal
expressed as $(R, G, B) = (200, 250, 130)$ may be converted to $(R, G, B, X) =$
 $(72, 122, 2, 128)$ and in this case all light sources Red, Green and Blue are turned on at
15 the fourth sub-frame. Here, the brightness of the back light can be varied as well as the
input value of the fourth sub-frame in "ST3". For example, if the light source Red is to
be turned on at the fourth sub-frame and the luminance of the light source Red is
changed from the gray level 128 into the gray level 110, the image signal expressed as
 $(R, G, B) = (200, 50, 50)$ can be converted to $(R, G, B, X) = (90, 50, 50, 110)$ as well as
20 $(R, G, B, X) = (72, 50, 50, 128)$. In addition, a selection condition that the average
luminance value should be larger than the gray level 128 can be changed, and although
the algorithm in the example of FIG. 9 is made on the basis of an average luminance of

the full screen, the selection of the color to be displayed in the fourth sub-frame can be made on the basis of the maximum luminance of the full screen. The steps "ST2" and "ST3" are controlled by the image signal processor. (shown in FIG. 7). The back light for the present invention is selected from the wave guide mode or the directly-underlaid mode described in FIGs. 3A and 3B, and the on-and-offs of light sources can be controlled by the image signal processor. Even though the algorithm of FIG 9 is one of embodiments suggested in order to explain the present invention, various algorithms having different conditions can be made in the method of color image display for the present invention without departing from the spirit or scope of the invention.

[0045] FIG. 10 is a plan view showing divided driving areas of the field sequential liquid crystal display device according to the present invention. The liquid crystal panel 200 may be divided into n number of divided driving areas "N1", "N2",, "Nn". The number of driving areas n is dependent on the degree of resolution of the liquid crystal display device and response time of the liquid crystal. The driving speed and the luminance of the liquid crystal display device according to the present invention can be increased by dividing a driving area and turning on each of light sources Red, Green and Blue for every divided driving area, whereas in the conventional field sequential liquid crystal display device, each of light sources is turned on one time for a frame as described in FIG. 4B. In addition, the one frame is divided into four sub-frames having a period of one-fourth of one frame period. Both the number of divided driving areas for liquid crystal panel and the number of light sources Red, Green and Blue of the back light do not need to be the same, and the number of divided driving areas for light

sources Red, Green and Blue of the back light may actually be designed with a fewer number.

[0046] FIG. 11 is a schematic diagram illustrating a driving method for divided driving areas for a field sequential liquid crystal display device according to the present

5 invention. As shown in the figure, the back light is turned on after the response of thin film transistor T and liquid crystal at every divided driving area. A period of a sub-frame consists of a scanning time, a response time of the liquid crystal and a flashing time of the back light. This relation can numerically be expressed as follow:

$$1/4f(220) = t_{TFT}(222) + t_{LC}(224) + t_{BL}(226)$$

10 where f is a frame frequency, t_{TFT} is a scanning time for all thin film transistors of sub-frame, t_{LC} is a response time of the assigned liquid crystal, and t_{BL} is a flash time of the back light. The scanning time of thin film transistors of each light source for all the divided driving areas is $t_{TFT'}$ (221). When the back light is turned on in a sequence of R, G, B and X, each of light sources is turned on in a sequence as follows:

15 R of N1, R of N2,, R of Nn, G of N1, G of N2,, G of Nn, B of N1, B of N2,, B of Nn, X of N1, X of N2,, X of Nn.

The light source X is a light source which is made from the combination of light sources of three or fewer colors of R, G and B and is to be turned on at the fourth sub-frame. The second divided driving area N2 is decided by the degree of resolution of a screen and response time of the liquid crystal. A time interval t_D (300) between driving sections of a previous light source and a next light source is also dependent on the

degree of resolution of the screen and the response time of the liquid crystal. This time interval $t_D(300)$ is formed between driving sections of light sources of divided driving areas from N_2 to N_n , but not in the first divided driving area N_1 . The time interval $t_D(300)$ is formed in order to remove an effect of a leakage of light generated when the back light is flashed before the liquid crystal for next light source is aligned, and the value of the time interval $t_D(300)$ is dependent on the response time of the liquid crystal. For example, when Optically Compensated Birefringent (OCB) mode is selected for the liquid crystal the time interval $t_D(300)$ may be 0.5 ~ 1msec. Because four light sources Red, Green, Blue and X are used in the present invention, it is possible to accomplish a higher luminance. And because it is possible to compensate a retarded response time of the liquid crystal and thus protect the leakage of light by driving the liquid crystal display device according to divided driving areas, the present invention can provide a liquid crystal display device having an image of higher qualities.

[0047] FIG. 12 is a schematic diagram showing a color coordinates of a color gamut of the field sequential liquid crystal display device according to the present invention. If only light sources Red, Green and Blue are used for the liquid crystal display device, a color range that can be actually displayed is narrower than a color range that a human observer can perceive. But if a light source displaying a fourth color is added, a color gamut that can be displayed is able to be broadened. As shown in the figure, four dots (R, G, B and C') mean positions of color coordinates of light sources Red, Green, Blue

and C'. A color coordinate region I is formed with light sources Red, Green and Blue and a color coordinate region II is formed with the fourth color C' added. Because the color coordinate region II cannot be made with only three light sources Red, Green and Blue, the color gamut that can be displayed becomes broadest when the color C' is close to the color Cyan, which is between a color of Green and Blue. That is, if four light sources Red, Green, Blue and C' are used, and the light source C' is turned on at the fourth sub-frame, the color gamut that is to be displayed can be broadened. The field sequential liquid crystal display device according to the FIG. 12 has a same structure as that of the field sequential liquid crystal display device according to the FIG. 7, but the present embodiment according to the FIG. 12 has four light sources for four colors.

[0048] A display device including light sources Red, Green and Blue and being sequentially driven according to the present invention will be taken for an example in the following. FIGs. 13A and 13B are schematic diagram illustrating a projector system, for example, among field sequential liquid crystal display devices according to the present invention. The projector system is one of color image display devices which enlarges and then projects various moving images or stationary images transmitted from such electronic goods as video player, television set and computer, and is expected to be broadly used for domestic uses, for example, at various meetings or playing movies in the small theater. FIG. 13A shows a reflective type projector system and this field sequential reflective projector system 310 comprises an image generator 312, light sources Red, Green and Blue 314 sequentially driven and for irradiating light

to the image generator 312, a dichroic mirror 316 for gathering and transmitting a light from light sources 314 to the image generator 312, a lens 317 for enlarging and controlling an image formed at the image generator 312, and a screen 318 to which the image of the image generator 312 is projected through the lens 317. A reflective type liquid crystal display device and Digital Light Processing (DLP) devices, for example, may be used for the image generator 312 of the reflective type projector system.

Though the reflective type liquid crystal display device is an image display device displaying an image using external light without the back light, the liquid crystal display device used for the reflective type projector system displays an image using light sources Red, Green and Blue. Because the Digital Light Processing (DLP) device is an image display device displaying an image using the principle of reflection of a mirror, the efficiency of use of light is high.

[0049] FIG. 13B shows a transmissive type projector system and this field sequential transmissive projector system 320 comprises an image generator 322, light sources Red, Green and Blue 324 sequentially driven for irradiating light to the image generator 322, a dichroic mirror 326 gathering and transmitting a light from light sources 324 to the image generator 322, a lens 328 for enlarging and controlling an image formed at the image generator 322, and a screen 330 to which the image of the image generator 322 is projected through the lens 328. A transmissive liquid crystal display device, i.e., a conventional liquid crystal display device, may be used for the image generator of the transmissive type projector system. Though the light sources Red, Green and Blue are

[0050] It will be apparent to those skilled in the art that various modifications and variations can be made in the field sequential liquid crystal display device and the

25